

## GM-H40L2G LCD 40 Monitor, W-XGA

Highly reliable 40" Professional LCD Display Monitor.



[Description](#)

[Main features](#)

[Additional features](#)

[Technical specs](#)

[Accessories](#)

[Brochures and manuals](#)

[See all in one page](#)



## Description

Highly reliable 40" Professional LCD Display Monitor, which gives excellent performance. Its slim design, with side venting, allows for flexible mounting possibilities, including space-saving flush mounting.

## Main features

- Wide range of inputs and control connectors ensures systems can be created with ease
- Slim design with side-vent cooling for flush mounting
- Easily replaceable bezel for applying custom colours
- No screen burn-in
- Self-diagnostic indicator lights
- High-speed input switching
- Digital zoom function
- Eco sensor available for self-adjusting brightness level
- Pro version picture-in-picture and picture-by-picture displays

## Additional features

- Power-on delay function (reduces the load on the studio's main power supply when multiple units are powered up simultaneously)
- Variety of external control terminals
- Anti-theft security lock
- VESA FDMI standard compliant fixture points

## Technical specs

### Alignment

Landscape / Portrait

### Screen Size:

40"

### Format:

16:9

### Resolution:

1,366 x 768 pixel

### Display Colours:

16.7 million colours (8 bit)

### Viewing Angle:

170° typical

### Contrast Ratio:

1.000 .1

### Brightness:

400 cd/m<sup>2</sup> max

### Video Standards

PAL/SECAM/NTSC,

PAL60, NTSC 4.43, PLA-M, PAL-N

### Tuner

w/o

### Input connectors:

PC:/Video: VGA to UXGA

DVI: VGA to UXGA (no HDCP)

CVBS, analogue RGB (optional)

### Loop-through option

n/a

### Video inputs:

1x Y/C or CVBS

1x RGB/HV or 1X YUV

1x DVI  
(more inputs through optional boards)

Audio input:  
PC: 3.5mm jack  
AV: chinch

Audio output:  
chinch

Speakers:  
3.4W + 3.4W (6 Ohm)

Remote control:  
IR: Yes / manual control: Yes

Interface  
RS-232C (in)

On screen Menu:  
Yes (5) multilingual

Multiscreen  
max. 2 x 2

Timer function  
Yes

Screen -saver  
Yes

Inverse picture function  
No

FAN / Cooler  
Yes

Mains switch  
Yes

Operating Humidity:  
20% to 80% (non-condensing)

Mains switch  
Yes

Power requirement:  
200 /240 VAC

Power consumption:  
330 W

Dimensions:  
595 x 986 x 123mm (+/-3mm)

Weight:  
26.8 kg +/- 10% (W/O stand)

Other:  
270108/ds

## Accessories

- [IF-CF01CMG](#)
- Component & RGB
- [IF-CF01PNG](#)
- Composite GM-H40Lxx
- [IF-CF01RBG](#)
- RGB/Component active-through
- [IF-CF21HDG](#)
- HD/SD SDI emb. Audio
- [TS-CL03SG](#)
- Stand Unit GM-H40L series

- [TS-CV20WG](#)
- Wall Mount, GM-H40L series

## Brochures and manuals



[Brochure for GM-H40L2G](#)



[Large HD LCD brochure](#)



[Instruction manual \(from the JVC Professional Europe Service Information System\)](#)

## Links

## Miscellaneous